

Pipe Line De-Coilers

Allflow Systems & Solutions have now added a range of custom HDPE Pipe de-coilers to our rapidly expanding range of equipment available for hire or purchase. These de-coilers have been engineered & field tested for the most rugged of conditions, providing the industry with a new unrivalled, cost effective, efficient & safe approach to laying coiled polyethylene pipe. The incorporation of modern straightening technology provides safe & efficient installation, decreasing labour requirements & lowering risks involved with medium bore coiled polyethylene pipe. Our current fleet range has the ability to process pipe from 50mm (2") in diameter up to a huge 160mm (6") in diameter with a safe working load (SWL) of up to 500kg. Custom configurations & additional features can be optioned to tailor these products according to your requirements.



Trailer & Skid Mounted

Skid mounted de-coiling units available for hire with mechanical pipe straightener. Use of straightening equipment provides safe & efficient installation, decreasing labour requirements & lowering risks involved with smaller bore polyethylene pipe. This unit has the ability to de-coil pipe from 50mm in diameter to 75mm in diameter. These skid mounted units are a very versatile machine the use of the fork pockets allow it to be held by an all terrain style forklift whilst the the coil is towed in position using a secondary vehicle, or the unit can be fixed to the tray of a utility vehicle & the pipe can be fixed to a stationary object & de-coiled as the vehicle moves.

Specifications:

Pipe Capacity: 50mm-75mm
Pipe Length: 200m (2500mm Dia)
SWL: 300kg

Trailer Mounted

Trailer mounted de-coiling units available for hire with hydraulic pipe straightener. Use of straightening equipment provides safe & efficient installation, decreasing labour requirements & lowering risks involved with medium bore polyethylene coiled pipe. This machine has the ability to de-coil pipe from 90mm in diameter to a huge 160mm (6') & has a SWL of 500kg.

Specifications

Pipe Capacity: 90mm-160mm
Pipe Length: 100m (3100mm Dia)
SWL: 500kg

PE Pipe Towing Heads

Towing heads available for hire to suit HDPE pipe from 50mm-160mm. Towing heads are a safe & reliable method of mechanically restraining pipe ends for use with pipe de-coilers, directional drills & other applications where pipe ends must be securely held whilst minimising damage to wall structure of the pipe.

Specifications:

Pipe Capacity: 50mm-160mm



Call us today to discuss your needs P: 02 6351 2877 info@allflowsystems.com.au

www.allflowsystems.com.au